

CV-CC2096

Rear Vision Camera



- 1/3.2" Format Camera
- 700 TV lines Horizontal Resolution
- Automatic Gain Control(AGC)
- 2.3 mm Board Lens
- Electronic Shutter Control 1/60(1/50)-1/100,000 Sec
- High Sensitivity With Min. Scene Illumination 0Lux At F2.0
- Wide Operating Temperature Range -20°C To 70°C
- Aluminum Die-cast Chassis
- Compact, Solid-state Body In Lightness
- Optional Audio Feature
- Class IP67 Weatherproof

Specifications

Model	CV-CC2096
Pick up device	1/3.2" Image Sensor
Total Pixels	1297 (H) x 977 (V)
Effective Pixels	1280(H) x 960(V)
Resolution	700 TV lines
Synchronization	Internal
Scanning System	2:1 Interlace
S / N Ratio	More than 50 dB
Electronic Shutter	Auto / manual 1 / 60 (1 / 50) ~ 1 / 100,000 sec.
Gamma Correct	0.45 / 1 (set to 0.45 before shipment)
Min. Illumination	0Lux (F2.0) with IR LED ON
Video Output	Composite 1.0 Vp-p / 75 ohm
AGC	ON
Aperture Correction	Yes
LED	4 PCS
Lens Type	Board lens : 2.3mm
View Angle	H:128° / V:92°
Power Source	DC 12V
Power Consumption	3W (Maximum)
Dimension	79 (W) mm x 54.7 (D) mm x 56 (H) mm
Operating Temperature	-20°C ~ 70°C (-4°F ~ 158°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Weatherproof	IP67

